


### 1.1 Balken – HEA

Profiel	Afmeting in mm						m <sup>2</sup> verf oppervl. p/m	Gewicht in kg p/m	
	h	x	b	x	d	x			t
100	96	x	100	x	5,0	x	8,0	0,561	17,10
120	114	x	120	x	5,0	x	8,0	0,677	20,30
140	133	x	140	x	5,5	x	8,5	0,794	25,20
160	152	x	160	x	6,0	x	9,0	0,906	31,00
180	171	x	180	x	6,0	x	9,5	1,024	36,20
200	190	x	200	x	6,5	x	10,0	1,136	43,20
220	210	x	220	x	7,0	x	11,0	1,255	51,50
240	230	x	240	x	7,5	x	12,0	1,369	61,50
260	250	x	260	x	7,5	x	12,5	1,484	69,50
280	270	x	280	x	8,0	x	13,0	1,603	77,90
300	290	x	300	x	8,5	x	14,0	1,717	90,00
320	310	x	300	x	9,0	x	15,5	1,756	99,50
340	330	x	300	x	9,5	x	16,5	1,795	107,10
360	350	x	300	x	10,0	x	17,5	1,834	114,20
400	390	x	300	x	11,0	x	19,0	1,912	127,40
450	440	x	300	x	11,5	x	21,0	2,011	142,70
500	490	x	300	x	12,0	x	23,0	2,110	158,00
550	540	x	300	x	12,5	x	24,0	2,209	169,20
600	590	x	300	x	13,0	x	25,0	2,308	181,40
650	640	x	300	x	13,5	x	26,0	2,407	193,70
700	690	x	300	x	14,5	x	27,0	2,505	207,90
800	790	x	300	x	15,0	x	28,0	2,700	228,30
900	890	x	300	x	16,0	x	30,0	2,900	256,90
1000	990	x	300	x	16,5	x	31,0	3,100	277,20



**Balkstaal HEA**

Kwaliteit  
 S235JRG2 volgens EN 10025.

Lengte  
 Uit voorraad leverbaar tot 24 meter.

